

1. GENERAL

- 1.1. It is mandatory that each rally vehicle to have properly installed and working “RALLY SAFETY SYSTEM” on board of the racing vehicle.
- 1.2. The system is rented at the administrative check and it is installed and sealed by the organizer at the scrutineering.
- 1.3. A deposit published in the supplementary regulations must be paid in cash only at the administrative check. Deposits are refunded in cash at sight when the equipment is returned to the organizer in working condition.
- 1.4. The tracking devices will be dismantled by the organizer in the last Parc Ferme or Time control. If a crew retires the rally, they can dismantle the Rally Safety System without causing any damage to the hardware and return it to the HQ, where after checking of the condition of the devices and hardware, the deposit will be refunded.
- 1.5. Crews will receive special Base/Mounting brackets for the Com-Box unit, that must be installed according to this appendix on the rally vehicle before entering the scrutineering.

1.6. It is the competitor's responsibility to ensure that the Rally Safety System always remain permanently connected and switched on with the antenna connected throughout the duration of the rally. Any crew that fails to do so, or if it is noted that the system is not in operation through the fault of the crew, will be reported to the Clerk of the Course and will incur a penalty of at least 15 minutes, which may be increased at the discretion of the Stewards.

2. SYSTEM COMPONENTS

- 2.1. GPS Tracker – 75 x 75 x 30 mm. Installed by the organizer at scrutineering on the required position. The device is IP 67 protected and have built in battery providing back up power if the external power is lost. See bellow possible installation locations and positions.
- 2.2. Com-Box – 75 x 75 x 30 mm. Installed by the organizer at scrutineering on the required position. The device is IP 67 protected and have built in battery providing back up power if the external power is lost. See bellow possible installation locations and positions.
- 2.3. Buzzer/Alarm – 55 x 55 x 70 mm. Installed by the organizer at scrutineering on the required position. See bellow possible installation locations and positions.
- 2.4. Base/Mount bracket for Com-box – 75 x 75 x 25 mm. Given at the administrative check, Installed by Crew on the required position before entering scrutineering. See bellow possible installation locations and positions.
- 2.5. RF extension and antenna installed on the buzzer/alarm or Com-box

